


版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)



技术参数 (Technical Data)				
UL	应用组别(Use group)	B	C	D
	额定电器参数 (Rated Electrical Parameters)	300V/20A	300V/20A	300V/20A
IEC	过压类别 (Overvoltage Category)	III/3	III/2	III/2
	/污染等级 (Pollution Degree)	III/3	III/2	III/2
额定电器参数 (Rated Electrical Parameters)		500V/32A	500V/32A	500V/32A
压线范围(Wire Range)		/		
工频耐压(Frequency Voltage)		AC 2500V		
冲击耐压(Rated Surge Voltage)		4000V		
绝缘阻抗 (Insulation Resistance)		DC500V 500MΩ above		
接触电阻(Contact Resistance)		$\leq 20m\Omega$		
剥线长度(String Length)		/		
工作温度(Temperature)		$-40^{\circ}C \sim +105^{\circ}C$		
额定扭矩(Rated torque)		/		
材质和电镀(Material and plating)				
绝缘材质(Housing)		PA66		
导体材料(Contact)		铜合金, 镀锡(Copper alloy, Sn plated)		
/		/		

产品命名编码:
(Product Number Code):

BT4-XX-1100-65CM-YY

系列(Series)

极数 (NO. of poles)

型号(Model)

塑体颜色(Housing Color)

端子间距(Pitch)

1:绿色(Green)	7:透明色 (Transparent)
2:蓝色(Blue)	8:白色(White)
3:黑色(Black)	9:黄色(Yellow)
4:灰色(Grey)	Y:多种颜色 (Mixed color)
5:橙色(Orange)	
6:红色(Red)	

P=11.00mm,N为孔位数(N for hole digits),有效位数为(Significant Digits):02p-19p

N	02P	03P	04P	05P	06P	07P	08P	09P	10P
L	46.00	57.00	68.00	79.00	90.00	101.00	112.00	123.00	134.00
B	11.00	22.00	33.00	44.00	55.00	66.00	77.00	88.00	99.00
N	11P	12P	13P	14P	15P	16P	17P	18P	19P
L	145.00	156.00	167.00	178.00	189.00	200.00	211.00	222.00	233.00
B	110.00	121.00	132.00	143.00	154.00	165.00	176.00	187.00	198.00



东莞市奥斯电子有限公司
DONGGUAN AOSI ELECTRONICS CO., LTD.

公差范围(Tolerance Range)

150~ ±1.50

60~150 ±1.00

型号(Type): BT4-XX-1100-65CM-YY

30~60 ±0.60

6~30 ±0.40

核准(Approval):

图号(Drawing NO.):

0~6 ±0.25

核审(Audit):

单位(Units):mm

页码(Page):1/1

角度 X ±2°

(Angle) X.X ±1°

设计(Design)

比例(Scale):FULL



版次(Version):T0